



CMF-X3275B

CMF-X3275B

IR P/T Dome Camera
 RS485 Control Pan/Tilt
 24 pieces IR-LED
 Illuminate distance >20m

Optional Model
 EC-D3875B, 1/3 Inch SONY 480tvl

Specification

Model No.	CMF-X3875B	CMF-X3275B
Camera Type	Color Pan/Tilt Dome Camera	
Image Sensor	1/3 Inch SONY Hi-Res. CCD	1/3 Inch SONY SuperHAD CCD
Effective Pixels	PAL:752(H) x582(V) 440K NTSC:768(H) x494(V) 380K	PAL:500(H) x 582(V) 290K NTSC:510(H) x 492(V) 250K
Sensing Area	4.9mm x 3.7mm	
Signal System	PAL /NTSC	
Horizontal Resolution	480 TV Lines	420 TV Lines
Min. Illumination	0.4 Lux/F1.2(IR OFF)	0.5 Lux/F1.2(IR OFF)
Lens Mount	Board lens 6mm/F2.0	
Iris Control	Fixed Iris	
S/N Ratio	More Than 48dB (AGC Off)	
Electronic Shutter	1/50(1/60) ~ 1/10,000 Sec.	
White Balance	Auto	
AGC	Auto	
Pan Speed	0°-12°/s	
Tilt Speed	0°-12°/s	
Pan Range	360°	
Tilt Range	90°	
Communication	Multi-Protocol,RS485	
Infrared Luminary	24 pieces IR-LED	
Illuminate istance	More than 20 M	
Supplied Voltage	DC12V Voltage	
Power Consumption	Less than 130mA	
Dimensions	ϕ 118 x106mm	
Weight	Approx.0.72kg	