

CMF SISTEMI DI SICUREZZA VIDEOSORVEGLIANZA



Model No.	CMF3216II
Camera Type	Color Weatherproof IR Camera
Image Sensor	1/3 Inch SONY SuperHAD CCD
Effective Pixels	PAL:500(H) x 582(V) 290K NTSC:510(H) x 492(V) 250K
Sensing Area	4.9mm x 3.7mm
Signal System	PAL /NTSC
Horizontal Resolution	420 TV Lines
Min. Illumination	Color(0.5 Lux), B/W(0 Lux,IR On)
Lens Mount	Varifocal 4-9mm Lens/F1.4
S/N Ratio	More Than 48dB (AGC Off)
Electronic Shutter	1/50(1/60) ~ 1/10,000 Sec.
White Balance	Auto
AGC	Auto
Infrared Luminary	48 pieces IR-LED
Infrared Wavelength	850 nm
Illuminate Distance	40m~45m
Waterproof Criterion	IP66
I/O Connector	Power : DC Power Jack , Video Output : BNC
Video Output Level	1.0 Vp-p (75 Ohms, composite)
Supplied Voltage	DC12V Voltage
Power Consumption	IR On: 280mA max., IR Off: Less than 130mA

CMF SISTEMI DI SICUREZZA VIDEOSORVEGLIANZA

Dimensions	160 x 100x97mm
Weight	Approx. 1.0kg