



**CMF-3206B**

- Externally adjust for Zoom&Focus
- Varifocal 4-9mm Lens
- 30pieces IR-LED
- Illuminate distance 30-40m
- IP66 Weatherproof

Optional Model

CMF3806B,1/3" SONY CCD,480 TVL

CMF-3206B

Specification

Model No.	CMF-3806B	CMF-3206B
Camera Type	Color Weatherproof IR Camera	
Image Sensor	1/3 Inch SONY Hi-Res. CCD	1/3 Inch SONY SuperHAD CCD
Effective Pixels	PAL:752(H) x582(V) 440K NTSC:768(H) x494(V) 380K	PAL:500(H) x 582(V) 290K NTSC:510(H) x 492(V) 250K
Sensing Area	4.9mm x 3.7mm	
Signal System	PAL /NTSC	
Horizontal Resolution	480 TV Lines	420 TV Lines
Min. Illumination	Color(0.4 Lux), B/W(0 Lux,IR On)	Color(0.5 Lux), B/W(0 Lux,IR On)
Lens Mount	Varifocal 4-9mm Lens/F1.4	
Iris Control	Manual Iris (Option Auto Iris)	
S/N Ratio	More Than 48dB (AGC Off)	
Electronic Shutter	1/50(1/60) ~ 1/10,000 Sec.	
White Balance	Auto	
AGC	Auto	
Infrared Luminary	30 pieces IR-LED	
Infrared Wavelength	850 nm	
Illuminate Distance	More than 30-40 M	
Waterproof Criterion	IP66	
I/O Connector	Power : DC Power Jack , Video Output : BNC	
Video Output Level	1.0 Vp-p (75 Ohms, composite)	
Supplied Voltage	DC12V Voltage	
Power Consumption	IR On: 280mA max., IR Off: Less than 130mA	