



CMF-X3262

**CMF-X3262**

- 1/3 inch Sony CCD
- 420 TVL,0.5 Lux/F1.2
- 6mm/F1.4 Fixed Iris Lens
- Dimension:110mm(  $\phi$  ) $\times$ 100mm(H)
- Power Requirement:DC12V

Optional Model

- CMFX3862,1/3" SONY CCD,480 TVL
- CMFX4262,1/4" SONY CCD,420 TVL
- CMFX4062,1/4" SHARP CCD,420 TVL

Specification

Model No.	CMF-X3862	CMF-X3262	CMF-X4262	CMF-X4062
Camera Type	Color Plastic Dome Camera			
Image Sensor	1/3 Inch SONY Hi-Res. CCD	1/3 Inch SONY SuperHAD CCD	1/4 Inch SONY SuperHAD CCD	1/4 Inch SHARP CCD
Effective Pixels	P:752 x582 N:768 x494	PAL:500(H) x 582(V) 290K NTSC:510(H) x 492(V) 250K		
Sensing Area	4.9mm x 3.7mm		3.6mm x 2.7mm	
Signal System	PAL /NTSC			
Horizontal Resolution	480 TV Lines	420 TV Lines		
Min. Illumination	0.4 Lux/F1.2	0.5 Lux/F1.2	0.8 Lux/F1.2	
Lens Mount	CS 6mm/F1.4 Fixed Iris lens(optional 4/6/8mm)			
S/N Ratio	More Than 48dB (AGC Off)			
Electronic Shutter	1/50(1/60) ~ 1/10,000 Sec.			
White Balance	Auto			
AGC	Auto			
I/O Connector	Power : DC Power Jack , Video Output : BNC			
Video Output Level	1.0 Vp-p (75 Ohms, composite)			
Supplied Voltage	DC12V Voltage			
Power Consumption	Less than 130mA			
Dimensions	$\phi$ 110 x100mm			
Weight	Approx. 0.36kg			